

Emerg. luminaire EE 1x1W ERT-LED 3h 230V AC Wireless radial


White, with round cover, ceiling recessed mounting with metal springs and external electronic box, security luminaire to illuminate areas with a luminaire distance of 10m at a mounting high of 2,5m, with wireless central switching function



Technische Daten

Hoogte (mm)	23,00
Netto diameter (mm)	88,00
Nettogewicht (kg)	0,35
Type verlichting	Noodverlichting
Type batterijvoeding	Autonome batterij
Type toestel	WirelessControl Professional
Uitvoering	Verlichting metaal
Design	EE
Afwerking	Wit
Autonomietijd (h)	3
Lichtmiddel	ERT-LED (1W)
Lumen	140
Nominale spanning (V)	230VAC 50Hz ±20%
Batterij type (V/Ah)	4,8/2,0 NiMh
Beschermingsgraad	IP20
Bevestiging	Plafondinbouw
Omgevingstemperatuur min. (°C)	-5
Omgevingstemperatuur max. (°C)	40
AA Klasse E 8101	AA4

Dimensions (mm)



Distance table - min. illumination at the middle line: 1lx - maintenance factor 0,80 -3h autonomy time

Montagehöhe [m]					
2,00	3,76	9,62	9,63	9,64	3,76
2,50	1,06	9,67	9,74	10,04	1,11
3,00	0,00	8,00	8,00	8,07	0,00

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Emerg. luminaire EE 1x1W ERT-LED 3h 230V AC Wireless radial White, with round cover, ceiling recessed mounting with metal springs and external electronic box, security luminaire to illuminate areas with a luminaire distance of 10m at a mounting high of 2,5m, with wireless central switching function	NLEER023W
Optionele toebehoren	
EE Sierafdekking noodverlichting vierkant wit	NLEEQWS
EE Sierafdekking noodverlichting vierkant wit	
EE Sierafdekking noodverlichting vierkant antraciet	NLEEQAZ
EE Sierafdekking noodverlichting vierkant antraciet	
EE Sierafdekking noodverlichting rond antraciet	NLEERAZ
EE Sierafdekking noodverlichting rond antraciet	
Batterij NiMH 4,8V 2,0Ah voor LPU-/LEM-module	NLAKKU4820
Vervangbatterij noodverlichting	