


KC Noodverlichting LED autonoom autotest 3h wand TT

Exit sign: wall mounting, safety light: ceiling mounting, viewing distance: 30m, 1h: 300lm; 3h: 300lm; 8h: 120lm, LiFePO4 battery suitable for low temperatures -15° to 40°C



Technische Daten


Netto lengte (mm)	357,00
Breedte (mm)	176,00
Hoogte (mm)	73,00
Nettogewicht (kg)	0,80
Type verlichting	Noodverlichting
Type batterijvoeding	Autonome batterij
Type toestel	Autotest lage temperatuur
Productgroep	Kunststof verlichting
Design	KC
Halogeenvrij	Behuizing van halogeenvrij kunststof
Kleur	RAL 9003
Pictogrammen	Set pictogrammen (pijl links, rechts, onder, boven) conform ISO 7010
Detectie afstand (m)	30

Technische Daten - Fortsetzung


Lichtmiddel	LED (3W)
Lumen	1h: 300;3h: 300;8h: 120
Nominale spanning (V)	230VAC 50Hz $\pm 20\%$
Continu vermogen (W)	5,70
Standby vermogen (W)	2
Maximaal vermogen (W)	6,90
Type batterij (V/Ah)	LiFePO4 2x 3,2V/ 3,3Ah-TT
Beschermingsgraad	IP54
Slagvastheid	IK06
Bevestiging	Wandbevestiging
Omgevingstemperatuur min. (°C)	-15
Omgevingstemperatuur max. (°C)	40
AA Klasse E 8101	AA4
Leverancier	Schrack

Dimensions (mm)

NLKCW...



Dimensions (mm)



Spacing table - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - Autonomy time 8h

					
2,00	2,46	6,23	6,29	6,34	2,48
2,50	2,52	6,76	6,82	6,88	2,58
3,00	2,44	7,13	7,16	7,19	2,57
3,50	2,30	7,23	7,27	7,36	2,43
4,00	2,03	7,04	7,25	7,44	2,17
5,00	1,09	6,50	6,73	6,92	0,98

Artikeltabelle

BEZEICHNUNG	BEST.NR.
KC Noodverlichting LED autonoom autotest 3h wand TT	
Exit sign: wall mounting, safety light: ceiling mounting, viewing distance: 30m, 1h: 300lm; 3h: 300lm; 8h: 120lm, LiFePO4 battery suitable for low temperatures -15° to 40°C	NLKCWPT03S
Optionele toebehoren	
KC Regendak plexiglas	NLKCRD
KC Inbouwkader beton noodverlichting	NLKCBERO
KC Inbouwkader noodverlichting	NLKCER00
Uitsnijding plafond: 320x150mm	
KC Dichting IP65 noodverlichting	NLKCIP65
KC Transparante deksel met hangpictogram	NLKCH
Batterij LiFePO4 3.2V 3.3Ah lage temperatuur	
LiFePO4 - Lithium-iron-phosphate battery suitable for low temperatures, UN3480 - LITHIUM-ION BATTERIES, The permissible ambient luminaire temperatures are specified for the low temperature luminaires	NLAKKU323T
Korf balbescherming KC/ KB/ KBG/ KX/ PF/ LX/ RX	NLBALL2
KC Pictogram links boven	NLKCPIKTLO
KC Pictogram links onder	NLKCPIKTLU
KC Pictogram rechts boven	NLKCPIKTRO
KC Pictogram rechts onder	NLKCPIKTRU
	NLTESTSC2
Protective cover for test buttons NLTEST2---	NLTEST2COV