

Datenblatt für Artikel: NLKCWS039M

Luminaire KC for CPS Mon.all Modes 4x1W ERT-LED 230V wall m.

Emergency luminaire without pictograms



Technische Daten

Luminaire type	safety luminaire
Self contained - central battery	central power supply luminaire
Function	with monitoring and mixing operation
Version	Plastic luminaire
Design	KC
Colour	White
Illuminant	ERT-LED (4W)
Lumen	520
Voltage range (V)	230V AC 50Hz $\pm 20\%$; 230V DC $\pm 20\%$
IP Rating	IP54
Mounting	surface mounting ceiling recessed mounting ceiling universal
Min. ambient temperature (°C)	-30
Max. ambient temperature (°C)	55
Net weight (kg)	1,10

Distance table - min. illumination at the middle line: 1 lx - maintenance factor 0,80

Montagehöhe [m]					
2,00	7,46	16,44	15,49	8,50	3,33
2,50	8,72	19,75	18,20	9,18	3,44
3,00	9,81	22,80	20,34	9,57	3,45
3,50	10,77	25,37	22,28	9,86	3,50
4,00	10,99	27,55	22,99	9,84	3,48
5,00	10,26	30,92	22,32	10,16	3,24
6,00	9,98	31,56	21,70	10,02	3,06
7,00	9,64	30,36	21,28	9,56	2,68
8,00	9,54	29,32	21,00	8,94	2,00
9,00	4,98	28,74	16,38	8,49	1,44
10,00	0,68	26,96	13,08	7,56	0,36

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Luminaire KC for CPS Mon.all Modes 4x1W ERT-LED 230V wall m. Emergency luminaire without pictograms	NLKCWS039M
Optional Accessories	
Rain cover for emergency luminaires Design KC plexiglass	NLKCRD
Concrete Plaster Box for Emergency luminaires Design KC	NLKCBERO
Recessed Frame for Emergency luminaires Design KC	NLKCER00
Adhesive pictograph Set for NLKC left, right, straight Suitable for luminaires design KC with opal diffusor	NLKC0103
IP65 Sealing for (NLKCW..)	NLKCIP65
Clear cover with hanging pictogram vd 24m for NLKCW..	NLKCH
Transparent Cover for Emergency luminaire Design KC	NLKCPR
Ball Protection for KC, KB+KBG, KX, PF, LX, RX	NLBALL2
Plug-pictogram left top for Design KC	NLKCPIKTLO
Plug-pictogram left bottom for Design KC	NLKCPIKTLU
Plug-pictogram right top for Design KC	NLKCPIKTRO
Plug-pictogram right bottom for Design KC	NLKCPIKTUR