


KW Noodverlichting autotest HP-LED 4x 1W

3h plafond

1h/3h adjustable, ceiling surface mounting with pictograms on one or two sides or for wall surface mounting with pictogram on one side, viewing distance: 16m, IP54, protection class II, 1h: 300lm; 3h: 300lm




Technische Daten

Netto lengte (mm)	390,00
Breedte (mm)	93,00
Hoogte (mm)	139,00
Nettogewicht (kg)	1,30
Type verlichting	Noodverlichting
Type batterijvoeding	Autonome batterij
Type toestel	Noodverlichtng met autotest
Type toestel	Kunststof verlichting
Design	KW
Halogeenvrij	Behuizing van halogeenvrij kunststof
Afwerking	Wit
Detectie afstand (m)	16

Technische Daten - Fortsetzung

Autonomietijd (h)	3
Lichtmiddel	LED (3W)
Lumen	1h: 300;3h: 300
Nominale spanning (V)	230VAC 50Hz $\pm 20\%$
Batterij type (V/Ah)	LiFePO4 2x 3,2V/ 3,3Ah
Beschermingsgraad	IP54
Bevestiging	Plafondmontage
Omgevingstemperatuur min. (°C)	-5
Omgevingstemperatuur max. (°C)	40
AA Klasse E 8101	AA4
Leverancier	Schrack

Afmetingen (mm)



Abstandstabelle 1h, 3h Autonomie - Min. Beleuchtungsstärke: 1lx - Wartungsfaktor 0,80

Montagehöhe [m]					
2,00	3,55	9,23	8,09	7,02	2,74
2,50	3,68	9,78	8,62	7,52	2,84
3,00	3,72	10,17	8,98	7,85	2,86
3,50	3,66	10,40	9,20	8,05	2,79
4,00	3,51	10,51	9,29	8,11	2,61
5,00	2,80	10,34	9,08	7,86	1,84

Abstandstabelle 8h Autonomie - Min. Beleuchtungsstärke: 1lx - Wartungsfaktor 0,80

Montagehöhe [m]					
2,00	1,95	5,66	5,00	4,37	1,48
2,50	1,70	5,66	4,99	4,34	1,20
3,00	0,99	5,42	4,73	4,06	0,42

Artikeltabelle

BEZEICHNUNG	BEST.NR.
KW Noodverlichting autotest HP-LED 4x 1W 3h plafond 1h/3h adjustable, ceiling surface mounting with pictograms on one or two sides or for wall surface mounting with pictogram on one NLKWD001SC side, viewing distance: 16m, IP54, protection class II, 1h: 300lm; 3h: 300lm	
Optionele toebehoren	
KW Korf balbescherming	NLBKW
Pendelpaar 500 mm wit bedraad	NL2PW
Pendelpaar 500 mm wit bedraad	
Wandbeugel voor KB/ KX/ KW/ KCD/ KE/ GX/ RX wit	NLAWX001
Wandbeugel voor KB/ KX/ KW/ KCD/ KE/ GX/ RX wit	