

Zentralbatt. MD Lad. 2,5A/0DCM

without el. circuit module NLDCM42MID, without batteries, with battery compartment upto 55 Ah, H1950 x W600 x D450mm



Technische Daten

Netto lengte (mm)	450,00
Breedte (mm)	600,00
Hoogte (mm)	1.950,00
Nettogewicht (kg)	105,00

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Zentralbatt. MD Lad. 2,5A/0DCM	NLMD0100
without el. circuit module NLDCM42MID, without batteries, with battery compartment upto 55 Ah, H1950 x W600 x D450mm	
Noodzakelijke toebehoren	
Mains circuit module DCM for 2 el. circuits 19" 2x1A	
For individually centrally switchable emergency luminaires NL..EL, NL...E, max. load 2 x 300VA – fuse 4x F5A, 6,3x32mm. Suitable NLDCM12E for LPS and CPS Micro-, Mini-, Midi-, Maxi- or MultiControl	
Stromkreiseins.2X3A ML DS/BS	NLDCM32
Max. load 2 x 650VA – fuse 4x F5A, 6,3x32mm. Suitable for LPS and CPS Micro-, Mini-, Midi-, Maxi- or MultiControl	
Stromkreiseins.2X4A ML DS/BS	NLDCM42
Max. load 2 x 860VA – fuse 4x F6,3A, 6,3x32mm. Suitable for LPS and CPS Mini-, Midi-, Maxi- or MultiControl	
Stromkreiseins.2X4A ML DS/BS	NLDCM42MID
Max. load 2 x 860VA – fuse 4x F6,3A, 6,3x32mm. Built in into MidiControl at the factory	

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Noodzakelijke toebehoren	
Battery set 216V 18 pcs. longlife OGIV 12V/17Ah incl. cables Type RPower, incl. cable connectors (NLBAV1728), battery set suitable for 1935W/1h 736W/3h 343W/8h, total weight: 99kg, ventilation requirements according to EN 62485-2: Q=0,79m³/h, A=22cm²	NLBAS017
Battery set 216V 18 pcs. longlife OGIV 12V/33Ah incl. cables Type RPower, incl. cable connectors (NLBAV1728), battery set suitable for 2678W/1h 1227W/3h 531W/8h, total weight: 166kg, ventilation requirements according to EN 62485-2: Q=1,2m³/h, A=33,5cm²	NLBAS026
Battery set 216V 18 pcs. longlife OGIV 12V/28Ah incl. cables Type RPower, incl. cable connectors (NLBAV1728), battery set suitable for 2575W/1h 1250W/3h 566W/8h, total weight: 164kg, ventilation requirements according to EN 62485-2: Q=1,34m³/h, A=37,4cm²	NLBAS028
Battery set 216V 18 pcs. longlife OGIV 12V/33Ah incl. cables Type RPower, incl. cable connectors (NLBAV3375G), battery set suitable for 3421W/1h 1411W/3h 635W/8h, total weight: 198kg, ventilation requirements according to EN 62485-2: Q=1,57m³/h, A=44,1cm²	NLBAS033
Battery set 216V 18 pcs. longlife OGIV 12V/41Ah incl. cables Type RPower, type RPower, incl. cable connectors (NLBAV3375-), battery set suitable for 4061W/1h 1630W/3h 719W/8h, total weight: 248kg, ventilation requirements according to EN 62485-2: Q=1,88m³/h, A=52,6cm²	NLBAS040
Battery set 216V 18 pcs. longlife OGIV 12V/44Ah incl. cables Type RPower, type RPower, incl. cable connectors (NLBAV3375-), battery set suitable for 4579W/1h 1884W/3h 862W/8h, total weight: 263kg, ventilation requirements according to EN 62485-2: Q=2,15m³/h, A=60,1cm²	NLBAS045
Battery set 216V 18 pcs. longlife OGIV 12V/57Ah incl. cables Type RPower, type RPower, incl. cable connectors (NLBAV3375-), battery set suitable for 6324W/1h 2598W/3h 1194W/8h, total weight: 310kg, ventilation requirements according to EN 62485-2: Q=2,83m³/h, A=79,2cm²	NLBAS055
Optionele toebehoren	
Plexiglas cover with lock for CPS Midicontrol	NLPLXMD
3-fasen Netüberw. mit Bus	NLMCLM
PC230 3-Fases-Netbewaking	NLPC2300
Light switch query module 8 inp.incl.mains monitor, separate	NLSAM24
Indicator panel with LCD clear text display and bus comm.	NLMCT15
Indicator panel with LCD display, key switch and bus comm. With key switch	NLMCT15S