

Datenblatt für Artikel: NLMN102A09

Low Power Supply MiniControl 2 circ. total max. 40 lamps

Max. load: 985W 1h / 403W 3h, optionally extenable to max. 12 electrical circuits 240
luminaires



Technische Daten

Netto lengte (mm)	230,00
Breedte (mm)	500,00
Hoogte (mm)	1.100,00
Nettogewicht (kg)	153,01

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Low Power Supply MiniControl 2 circ. total max. 40 lamps Max. load: 985W 1h / 403W 3h, optionally extenable to max. 12 electrical circuits 240 luminaires	NLMN102A09
Optionele toebehoren	
E30 Schrank für Gruppebatt. MN Outside dimensions: 1388 x 861 x 345mm (HxWxD), colour RAL7035, 115kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	NLMNE30
Plexiglas cover with lock for LPS Minicontrol	NLPLXMIN
3-fasen Netzüberw. mit Bus	NLMCLM
PC230 3-Fases-Netbewaking	NLPC2300
Light switch query module 8 inp.incl.mains monitor, separate	NLSAM24
Indicator panel with LCD clear text display and bus comm.	NLMCT15
Indicator panel with LCD display, key switch and bus comm. With key switch	NLMCT15S