

Datenblatt für Artikel: NLMN106A--

Low Power Supply MiniControl 6 circ. total max. 120 lumin.

6 electrical circuits, max. 120 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1 h / 500 W 3 h / 300 W 8 h, optionally expandable to max. 12 circuits max. 240 luminaires, h x w x d: 1100 x 500 x 230 mm



Technische Daten

Netto lengte (mm)	230,00
Breedte (mm)	500,00
Hoogte (mm)	1.100,00
Nettogewicht (kg)	140,01

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Low Power Supply MiniControl 6 circ. total max. 120 lumin.	
6 electrical circuits, max. 120 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1h / 500 W 3 h / 300 W 8 h, optionally expandable to max. 12 circuits max. 240 luminaires, h x w x d: 1100 x 500 x 230 mm	NLMN106A
Optionele toebehoren	
E30 Schrank für Gruppebatt. MN	
Outside dimensions: 1388 x 861 x 345mm (HxWxD), colour RAL7035, 115kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	NLMNE30
Plexiglas cover with lock for LPS Minicontrol	NLPLXMIN
3-fasen Netzüberw. mit Bus	NLMCLM
PC230 3-Fases-Netbewaking	NLPC2300
Light switch query module 8 inp.incl.mains monitor, separate	NLSAM24
Indicator panel with LCD clear text display and bus comm.	NLMCT15
Indicator panel with LCD display, key switch and bus comm. With key switch	NLMCT15S