

Datenblatt für Artikel: NLMN108A--

# Low Power Supply MiniControl 8 circ. total max. 160 lumin.

8 electrical circuits, max. 160 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1 h / 500 W 3 h / 300 W 8 h, optionally expandable to max. 12 circuits max. 240 luminaires, h x w x d: 1100 x 500 x 230 mm



## Technische Daten

|                   |          |
|-------------------|----------|
| Netto lengte (mm) | 230,00   |
| Breedte (mm)      | 500,00   |
| Hoogte (mm)       | 1.100,00 |
| Nettogewicht (kg) | 140,01   |

## Artikeltabelle

| BEZEICHNUNG                                                                                                                                                                                                                 | BEST.NR. |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| Low Power Supply MiniControl 8 circ. total max. 160 lumin.                                                                                                                                                                  |          |
| 8 electrical circuits, max. 160 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1h / 500 W 3 h / 300 W 8 h, optionally expandable to max. 12 circuits max. 240 luminaires, h x w x d: 1100 x 500 x 230 mm | NLMN108A |
| <b>Optionele toebehoren</b>                                                                                                                                                                                                 |          |
| E30 Schrank für Gruppebatt. MN                                                                                                                                                                                              |          |
| Outside dimensions: 1388 x 861 x 345mm (HxWxD), colour RAL7035, 115kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30                                             | NLMNE30  |
| Plexiglas cover with lock for LPS Minicontrol                                                                                                                                                                               | NLPLXMIN |
| 3-fasen Netzüberw. mit Bus                                                                                                                                                                                                  | NLMCLM   |
| PC230 3-Fases-Netbewaking                                                                                                                                                                                                   | NLPC2300 |
| Light switch query module 8 inp.incl.mains monitor, separate                                                                                                                                                                | NLSAM24  |
| Indicator panel with LCD clear text display and bus comm.                                                                                                                                                                   | NLMCT15  |
| Indicator panel with LCD display, key switch and bus comm.<br>With key switch                                                                                                                                               | NLMCT15S |