

PM Noodverlichting autotest LED 3h 230VAC wand TT

1h/3h/8h adjustable, wall surface mounting with pictograms, viewing distance: 20m, IP65, protection class II, LiFePO₄ battery suitable for low temperatures -15° to 40°C




Technische Daten

Netto lengte (mm)	236,00
Breedte (mm)	136,00
Hoogte (mm)	65,00
Nettogewicht (kg)	1,30
Type verlichting	Noodverlichting
Type batterijvoeding	Autonome batterij
Type toestel	Autotest lage temperatuur
Productgroep	Kunststof verlichting
Design	PM
Halogeenvrij	Behuizing van halogeenvrij kunststof
Kleur	RAL 9003
Pictogrammen	Pictogrammen conform ISO 7010 zijn inbegrepen
Detectie afstand (m)	20

Technische Daten - Fortsetzung

Lichtmiddel	LED (3W)
Nominale spanning (V)	230VAC 50Hz $\pm 20\%$
Continu vermogen (W)	5,70
Standby vermogen (W)	2
Maximaal vermogen (W)	6,90
Type batterij (V/Ah)	LiFePO4 2x 3,2V/ 3,3Ah-TT
Beschermingsgraad	IP65
Slagvastheid	IK06
Bevestiging	Wandbevestiging
Omgevingstemperatuur min. (°C)	-15
Omgevingstemperatuur max. (°C)	40
AA Klasse E 8101	AA4
Leverancier	Schrack

Dimensions (mm)



Artikeltabelle

BEZEICHNUNG	BEST.NR.
PM Noodverlichting autotest LED 3h 230VAC wand TT 1h/3h/8h adjustable, wall surface mounting with pictograms, viewing distance: 20m, IP65, protection class II, LiFePO4 battery suitable for low temperatures -15° to 40°C	NLPMWT03SC
Optionele toebehoren	
PM Inbouwkader noodverlichting wit Uitsnijding plafond: 246x152mm	NLPME
Batterij LiFePO4 3.2V 3.3Ah lage temperatuur LiFePO4 - Lithium-iron-phosphate battery suitable for low temperatures, UN3480 - LITHIUM-ION BATTERIES, The permissible ambient luminaire temperatures are specified for the low temperature luminaires	NLAKKU323T
	NLTESTSC2
Protective cover for test buttons NLTEST2---	NLTEST2COV