


Datenblatt für Artikel: NLZAAT08WB

ZA Noodverlichting WirelessConnect 4x 0,5W Power LED 8h

Zinc die-cast, anthracite, IP65, -25° up to 40°C, with LiFePO4 battery suitable for low temperatures, wall mounting, with Bluetooth communication, 85lm




Technische Daten

Netto lengte (mm)	315,00
Hoogte (mm)	140,00
Diepte (mm)	65,00
Nettogewicht (kg)	2,20
Type verlichting	Noodverlichting
Type batterijvoeding	Autonome batterij
Type toestel	WirelessConnect lage temperatuur
Productgroep	Verlichting metaal
Design	ZA
Kleur	RAL 7016
Autonomietijd (h)	8
Lichtmiddel	LED (2W)
Lumen	85


Technische Daten - Fortsetzung

Nominale spanning (V)	230VAC 50Hz $\pm 20\%$
Continu vermogen (W)	3,90
Standby vermogen (W)	1,50
Maximaal vermogen (W)	5,30
Type batterij (V/Ah)	LiFePO4-TT 3,2V/ 3,3Ah
Beschermingsgraad	IP65
Slagvastheid	IK08
Bevestiging	Wandbevestiging
Omgevingstemperatuur min. ($^{\circ}\text{C}$)	-25
Omgevingstemperatuur max. ($^{\circ}\text{C}$)	40
AA Klasse E 8101	AA3 AA4 AA5
Leverancier	Schrack

Dimensions (mm)



Drilling distances (mm)



**Spacing table - Min. illuminance on the center line +/- 0.5 m: 1 lx -
Maintenance factor 0.80 - Autonomy time 8h**

2,00	0,11	2,3	0,56	7,51	2,07
2,50	0,05	2,31	0,54	7,16	1,8

Artikeltabelle

BEZEICHNUNG	BEST.NR.
ZA Noodverlichting WirelessConnect 4x 0,5W Power LED 8h Zinc die-cast, anthracite, IP65, -25° up to 40°C, with LiFePO4 battery suitable for low temperatures, wall mounting, with Bluetooth communication, 85lm	NLZAAT08WB
Optionele toebehoren	
Batterij LiFePO4 3.2V 3.3Ah lage temperatuur LiFePO4 - Lithium-iron-phosphate battery suitable for low temperatures, UN3480 - LITHIUM-ION BATTERIES, The permissible ambient luminaire temperatures are specified for the low temperature luminaires	NLAKKU323T