

Datenblatt für Artikel: QLIES0500-

Switch DIN-Rail 4xRJ45 + 1xRJ45

12VDC-48VDC

4x 10/100Mbps, 1x 100Mbps



SCHRACK-Info

Overview

QLIES0500- Industry Ethernet Switch provides 5 ports of 10/100Base-TX Ethernet to enable high speed networking at mission-critical environment. This device is designed to be mounted on an industry standard DIN-rail, plus the clearly visible status LEDs provide simple monitoring of port link activity.

Cost Effective

This device operates under -10°C to 60°C (-14 to 140 Fahrenheit) temperature that offers optimal suitability for industrial applications at low cost while maintaining all components built to withstand harsh environment applications without compromise reliability without compromise reliability and stability.

Safety

With UL60950 standard complied that gives basic protection against electric shock, fire spread from within, ignition and burning, current circuit hazardous under normal and fault condition. As well as set of compliances to meet many EMC, isolation, vibration and shock standards.

Plug & Play

This unmanaged Industrial Ethernet Switch is designed for the demanding industrial environments at business in need of instant connectivity with no setup or configure required, truly plug and play.

Key-Features

- Provides flexibility of 5 x 10/100Base-TX ports

- -10°C to 60°C (-14°F to 140°F) and is tested for functional operation @-20°C to 70°C (-4°F to 158°F)
- 10/100Mbps Full-/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- Supports 12 to 48VDC Power inputs
- Complies with IEC61000-6-2 EMC Generic standard immunity for Industrial environment

Order-Information

- QLIES0500- 5 FE Unmanaged Switch -10 to 60, DIN-rail

Package Contents

- QLIES0500-
- Quick Installation Guide

Technische Daten

Breedte (mm)	26,00
Hoogte (mm)	110,00
Diepte (mm)	70,00
EAN CODE	4015867181591
Omgevingstemperatuur min. (°C)	0
Omgevingstemperatuur max. (°C)	70
Productgamma	Ethernet switch
Transmissiesnelheid	10/100Mbps
Aansluitingen	5
Bevestiging	DIN-rail

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Optionele toebehoren	
Schakelende voeding 230VAC/ 24VDC 30W 1,5A MOD Voeding modulaire uitvoering	QLPOW2410
Schakelende voeding 230VAC/ 24VDC 60W 2,5A MOD Voeding modulaire uitvoering	QLPOW2420
Schakelende voeding 230VAC/ 24VDC 75W 3,2A DIN-rail Voeding voor DIN-rail bevestiging	QLPOW2430
Schakelende voeding 230VAC/ 24VDC 120W 5A DIN-rail Voeding voor DIN-rail bevestiging	QLPOW2440
Schakelende voeding 230VAC/ 48VDC 120W 2,65A DIN-rail Voeding voor DIN-rail bevestiging	QLPOW4840
Schakelende voeding 230VAC/ 48VDC 240W 5A DIN-rail Voeding voor DIN-rail bevestiging	QLPOW4850
Schakelende voeding 230VAC/ 48VDC 480W 10A DIN-rail Voeding voor DIN-rail bevestiging	QLPOW4860
Schakelende voeding 230VAC/ 48VDC 64,8W 1,35A DIN-rail Voeding voor DIN-rail bevestiging	QLPOW4801