

Datenblatt für Artikel: SR1426220S

SORAX 19" Basicframe, RAL9005, W=600xD=1.200xH=2.000mm

42U, basic frame without planking parts



SCHRACK-Info

SORAX Server Enclosure


- Powder-coated enclosure (coarse structure - glossy)
- Enclosure: 12-fold profiled and welded
- Material: 1.5 - 2.5mm FE
- Color: Black RAL9005
- UV-resistant
- Maximum load with even distribution using cranked 19" profile rails: 2.000 kg
- Protection class: IP20 / IP54 depending on design
- Degree of protection enclosure: IK10
- Tested and built according to EN 62208 empty enclosure
- Installation height max. 2.000m above sea level
- Doors not included (can be ordered optionally)
- Side panels not included (can be ordered optionally)
- Base plate not included (can be ordered optionally)
- Roof plate not included (can be ordered optionally)
- 19" profile rails (4 pieces), galvanised and cranked (L-profile rails can be ordered as an option at no extra charge, reduced load capacity (1.200 kg with even distribution)), incl. height unit labelling
- 19" profile rails have a half pitch, depth-adjustable in 12.5mm increments
- 19" profile rail spacing can be extended to 23"

- 19" level spacing between rear of rack frame (inside) and rear 19" level: 175 mm
- 19" level spacing between rear and front 19" levels: 700 mm
- 19" level spacing between front 19" level and front of rack frame (inside): 75 mm
- 2x depth brace per side for various mounting options
- Earthing: Protection class I - earthing connection with earthing rail and earthing connections pre-wired in accordance with EN 61439-3 (applies to optionally mountable flat parts)
- Stable and precise design of the complete enclosure
- Prepared for optional cold aisle containment
- Server enclosure is delivered fully assembled depending on the configuration (individual enclosure test for function)
- Server enclosure can also be available as a demountable version (can be ordered as an option at extra cost SR1AD0026S)
- Server enclosure can be retroactively and individually expanded in depth (extension frame, e.g., 1.200mm to 1.400mm)

Technische Daten

Breedte (mm)	600,00
Hoogte (mm)	2.000,00
Diepte (mm)	1.200,00
EAN CODE	9004840998627
PRIJS	1.650,00
Kleur	RAL 9005
Hoogte eenheden	42
Beschermingsgraad	IP00
Leverancier	Schrack
Draagvermogen	2.000Kg
Type product	Serverkasten
Bijkomend vereist	Planking parts (as required)

**Maattekening: SORAX 19" Basicframe, RAL9005,
W=600xD=1.200xH=2.000mm**



BEZEICHNUNG	BEST.NR.
SORAX 19" Basicframe, RAL9005, W=600xD=1.200xH=2.000mm	SR1426220S
42U, basic frame without planking parts	