

Datenblatt für Artikel: SR3PDIEM01

PDU Essential Metered; 8xC13; 230V; 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/230V | 3,6kW
- Output: 8xC13 0° IEC Socket
- Supply cable: 2.0m | 1.5mm²
- with CEE7/7 angled plug
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Technische Daten

Netto lengte (mm)	437,40
Breedte (mm)	45,00

Technische Daten - Fortsetzung

Hoogte (mm)	60,00
Nettogewicht (kg)	1,10
EAN CODE	4057298233012
PRIJS	1.258,00
Omgevingstemperatuur min. (°C)	-5
Omgevingstemperatuur max. (°C)	45
Nominale spanning	230V
Beschermingsgraad	IP20
Type product	Metered Essential
Aantal stopcontacten	8
Type connector	8xC13
Nominale stroom (A)	16
Fasen per voeding	1
Aansluittype	CEE 7/7 (Type E/F)
Protocol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Bevestiging	Bevestigingshoek (L-vormig)

BEZEICHNUNG	BEST.NR.
PDU Essential Metered; 8xC13; 230V; 16A	SR3PDIEM01
Measurement per phase, incl. mounting bracket with screws	