

Datenblatt für Artikel: SR3PDIEM08

PDU Essential Metered; 24xC13; 4xC19; 230V; 32A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 32A/230V | 7,2kW Output: 24xC13 0° IEC Socket 4xC19 90° IEC Socket
- 2xMiniature Circuit Breaker C16A
- split into two blocks, each block
- fused with a MCB
- Supply cable: 3.0m | 4mm²
- with CEE 32A plug, blue
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Technische Daten

Netto lengte (mm)	1.170,60
Breedte (mm)	45,00
Hoogte (mm)	94,00
Nettogewicht (kg)	3,50
EAN CODE	4057298233104
PRIJS	1.640,00
Omgevingstemperatuur min. (°C)	-5
Omgevingstemperatuur max. (°C)	45
Nominale spanning	230V
Beschermingsgraad	IP20
Type product	Metered Essential
Aantal stopcontacten	28
Type connector	24 x IEC320 C13 und 4 x IEC320 C19
Nominale stroom (A)	32
Fasen per voeding	1
Aansluittype	CEE 32 A blauw
Protocol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Bevestiging	Bevestigingshoek (L-vormig)

BEZEICHNUNG	BEST.NR.
PDU Essential Metered; 24xC13; 4xC19; 230V; 32A	
Measurement per phase, incl. mounting bracket with screws	SR3PDIEM08