

Datenblatt für Artikel: SR3PDIPM05

# PDU PRO Metered, 24xC13, 6xC19, 400V, 16A, RCM

Measurement per phase, Residual Current Monitoring per phase, incl. mounting bracket with screws



## SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Residual Current Monitoring per phase, Typ B
- Input: 16 A / 400 V | 11 kW
- Supply cable: 3,0 m | 2,5 mm<sup>2</sup>
- with CEE Stecker 16 A red
- Output: 24 x C13 IEC Socket + 6 x C19 IEC Socket
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)

- Packed in cardboard box
- Length 1825 mm

## Technische Daten

|                                |                                                                                                                                                        |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Netto lengte (mm)              | 1.567,50                                                                                                                                               |
| Breedte (mm)                   | 56,00                                                                                                                                                  |
| Hoogte (mm)                    | 65,00                                                                                                                                                  |
| Nettogewicht (kg)              | 4,62                                                                                                                                                   |
| EAN CODE                       | 4057298207891                                                                                                                                          |
| PRIJS                          | 3.947,00                                                                                                                                               |
| Omgevingstemperatuur min. (°C) | 0                                                                                                                                                      |
| Omgevingstemperatuur max. (°C) | 50                                                                                                                                                     |
| Nominale spanning              | 400V                                                                                                                                                   |
| Beschermingsgraad              | IP20                                                                                                                                                   |
| Type product                   | Metered                                                                                                                                                |
| Aantal stopcontacten           | 30                                                                                                                                                     |
| Type connector                 | 24 x IEC320 C13 und 6 x IEC320 C19                                                                                                                     |
| Nominale stroom (A)            | 16                                                                                                                                                     |
| Fasen per voeding              | 3                                                                                                                                                      |
| Aansluittype                   | CEE 16 A rood                                                                                                                                          |
| Protocol                       | LDAP<br>IPv6<br>IPv4<br>DNS<br>SNMPv1<br>SSH<br>HTTP<br>SNMPv3<br>SNMPv2<br>NTP<br>SSH2<br>DHCP<br>ModBus /TCP<br>SMTP<br>HTTPS<br>SNMP Trap<br>Syslog |
| Bevestiging                    | Bevestigingshoek (L-vormig)                                                                                                                            |

| BEZEICHNUNG                                                                                      | BEST.NR.   |
|--------------------------------------------------------------------------------------------------|------------|
| PDU PRO Metered, 24xC13, 6xC19, 400V, 16A, RCM                                                   | SR3PDIPM05 |
| Measurement per phase, Residual Current Monitoring per phase, incl. mounting bracket with screws |            |