

Datenblatt für Artikel: SR3PDIPP01

# PDU PRO Metered+, 24xCombo Outlets (C13, C15, C19, C21), 230V, 16A

Metering per outlet, incl. mounting bracket with screws



## SCHRACK-Info

- PDU PRO Metered+
- Metering per socket
- Input: 16 A / 230 V | 3.6 kW
- Input: 3.0 m | 2.5 mm<sup>2</sup>
- with CEE plug 16 A blue
- Output: 24x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) &lt;/I

## Technische Daten

|                                |                                                                                                                                                        |
|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Netto lengte (mm)              | 1.191,00                                                                                                                                               |
| Breedte (mm)                   | 56,00                                                                                                                                                  |
| Hoogte (mm)                    | 71,00                                                                                                                                                  |
| EAN CODE                       | 4057298230257                                                                                                                                          |
| PRIJS                          | 4.638,00                                                                                                                                               |
| Omgevingstemperatuur min. (°C) | 0                                                                                                                                                      |
| Omgevingstemperatuur max. (°C) | 50                                                                                                                                                     |
| Nominale spanning              | 230V                                                                                                                                                   |
| Beschermingsgraad              | IP20                                                                                                                                                   |
| Type product                   | Metered+                                                                                                                                               |
| Aantal stopcontacten           | 24                                                                                                                                                     |
| Type connector                 | 24 x Combo Socket (C13/C15/C19/C21)                                                                                                                    |
| Nominale stroom (A)            | 16                                                                                                                                                     |
| Fasen per voeding              | 1                                                                                                                                                      |
| Aansluittype                   | CEE 16 A blauw                                                                                                                                         |
| Protocol                       | LDAP<br>IPv6<br>IPv4<br>DNS<br>SNMPv1<br>SSH<br>HTTP<br>SNMPv3<br>SNMPv2<br>NTP<br>SSH2<br>DHCP<br>ModBus /TCP<br>SMTP<br>HTTPS<br>SNMP Trap<br>Syslog |
| Bevestiging                    | Bevestigingshoek (L-vormig)                                                                                                                            |

| BEZEICHNUNG                                                        | BEST.NR.   |
|--------------------------------------------------------------------|------------|
| PDU PRO Metered+, 24xCombo Outlets (C13, C15, C19, C21), 230V, 16A | SR3PDIPP01 |
| Metering per outlet, incl. mounting bracket with screws            |            |