

Datenblatt für Artikel: SR3PDIPP03

PDU PRO Metered+, 18xCombo (C13, C15, C19, C21), 24xC13, 400V, 16A

Metering per outlet, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered+
- Metering per socket
- Input: 16 A / 400 V | 11 kW
- Supply cable: 3,0 m | 2,5 mm²
- with CEE plug 16 A red
- Output: 24x C13 IEC Socket + 18x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </l

Technische Daten

Netto lengte (mm)	1.678,20
Breedte (mm)	56,00
Hoogte (mm)	71,00
EAN CODE	4057298230325
PRIJS	6.550,00
Omgevingstemperatuur min. (°C)	0
Omgevingstemperatuur max. (°C)	50
Nominale spanning	400V
Beschermingsgraad	IP20
Type product	Metered+
Aantal stopcontacten	42
Type connector	24 x IEC320 C13 + 18 x Combo Socket (C13/C15/C19/C21)
Nominale stroom (A)	16
Fasen per voeding	3
Aansluittype	CEE 16 A rood
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Bevestiging	Bevestigingshoek (L-vormig)

BEZEICHNUNG	BEST.NR.
PDU PRO Metered+, 18xCombo (C13,C15,C19,C21), 24xC13, 400V, 16A	SR3PDIPP03
Metering per outlet, incl. mounting bracket with screws	