

Datenblatt für Artikel: SR3PDIPP07

PDU PRO Metered+, 36xCombo Outlet (C13, C15, C19, C21), 400V, 32A

Metering per outlet, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!



SCHRACK-Info

- PDU PRO Metered+
- Metering per socket
- Input: 32 A / 400 V | 22 kW
- Supply cable: 3,0 m | 4 mm²
- with CEE plug 32 A red
- Output: 36x Combo C13/C15/C19/C21
- 6x hydraulisch-magnetische LS-Schalter 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)

Technische Daten

Netto lengte (mm)	1.950,30
Breedte (mm)	56,00
Hoogte (mm)	71,00
EAN CODE	4057298230417
PRIJS	7.147,00
Omgevingstemperatuur min. (°C)	0
Omgevingstemperatuur max. (°C)	50
Nominale spanning	400V
Beschermingsgraad	IP20
Type product	Metered+
Aantal stopcontacten	36
Type connector	36 x Combo Socket (C13/C15/C19/C21)
Nominale stroom (A)	32
Fasen per voeding	3
Aansluittype	CEE 32 A rood
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Bevestiging	Bevestigingshoek (L-vormig)

BEZEICHNUNG	BEST.NR.
PDU PRO Metered+, 36xCombo Outlet (C13,C15,C19,C21), 400V,32A	SR3PDIPP07
Metering per outlet, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!	